




GCL-M6/60H

Cast Mono Module

300-335W



335W

Maximum Power Output


20.1%

Maximum Module Efficiency

0~+5W

Power Output Guarantee

Cell Type



5BB

12BB



More evenly distributed soldering points and better reliability and lower hot spot risk



Selected encapsulating material and stringent production process control ensure the product is highly PID resistant and snail trails free



Sand blowing test, salt mist test and ammonia test passed to endure harsh environments



Lower LID due to lower oxygen and carbon content



Special cell process ensures great performance under low irradiance conditions




Highly transparent self-cleaning glass brings additional yield and easy maintenance

GCL Delivers Reliable Performance Over Time

- World-class manufacturer of crystalline silicon photovoltaic modules
- Fully automatic facility and world-class technology
- Rigorous quality control to meet the highest standard: ISO9001:2015, ISO14001: 2015 and OHSAS: 18001 2007
- Tested for harsh environments (salt mist, ammonia corrosion and sand blowing test: IEC 61701, IEC 62716, DIN EN 60068-2- 68)
- Long term reliability tests
- 2x100% EL inspection ensuring defect-free modules

Linear Performance Warranty



* Please refer to GCL standard warranty for details

Additional Insurance Backed by Swiss RE



* Please refer to GCL for details

GCL-M6/60H

Cast Mono Module

300-335W

Electrical Specification (STC*)

	Pmax(W)	300	305	310	315	320	325	330	335
Maximum Power	Pmax(W)	300	305	310	315	320	325	330	335
Maximum Power Voltage	Vmp(V)	32.40	32.60	32.80	33.00	33.20	33.41	33.61	33.81
Maximum Power Current	Imp(A)	9.26	9.36	9.46	9.55	9.64	9.73	9.82	9.91
Open Circuit Voltage	Voc(V)	39.50	39.70	39.90	40.10	40.30	40.50	40.70	40.90
Short Circuit Current	Isc(A)	9.78	9.87	9.96	10.04	10.12	10.20	10.28	10.36
Module Efficiency	(%)	18.0	18.3	18.6	18.9	19.2	19.5	19.8	20.1
Power Output Tolerance	(W)	0~+5							

* Irradiance 1000W/m², Module Temperature 25°C, Air Mass 1.5

Electrical Specification (NOCT*)

	Pmax (W)	222.60	226.50	230.43	233.78	237.47	240.87	244.61	248.37
Maximum Power	Pmax (W)	222.60	226.50	230.43	233.78	237.47	240.87	244.61	248.37
Maximum Power Voltage	Vmp (V)	30.00	30.20	30.40	30.60	30.80	31.00	31.20	31.40
Maximum Power Current	Imp (A)	7.42	7.50	7.58	7.64	7.71	7.77	7.84	7.91
Open Circuit Voltage	Voc(V)	36.60	36.80	37.00	37.20	37.40	37.50	37.70	37.90
Short Circuit Current	Isc (A)	7.91	7.98	8.05	8.12	8.18	8.25	8.32	8.39

* Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

Mechanical Data

Number of Cells	60 Cells (6×10)
Dimensions of Module L*W*H (mm)	1666×1000×35mm [65.59×39.37×1.38 inches]
Weight (kg)	18.5 kg
Glass	High transparency solar glass 3.2mm [0.13 inches]
Backsheet	White
Frame	Silver, anodized aluminium alloy
J-Box	IP68 Rated
Cable	4.0mm ² [0.006 inches ²], 900mm [35.4 inches]
Number of diodes	3
Wind/ Snow Load	2400Pa/ 5400Pa*
Connector	MC Compatible

* For more details please check the installation manual of GCLSI

Temperature Ratings

Nominal Operating Cell Temperature (NOCT)	45±2°C
Temperature Coefficient of Isc	+0.06%/°C
Temperature Coefficient of Voc	-0.30%/°C
Temperature Coefficient of P _{MAX}	-0.39%/°C

Packaging Configuration

Module per box	30 pieces
Module per 40' container	840 pieces


Maximum Ratings

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC
Max Series Fuse Rating	20A


Optional

Connector: Original MC4


Module Dimension




Back View



I-V Curve at Different Temperature (335W)



I-V/P-V Curve at Different Irradiation (335W)



CAUTION: READ INSTALLATION MANUAL BEFORE USING THE PRODUCT



Contact Us for More Information

website: www.gclsi.com email: gclsales@gclsi.com